

# CONTAINER FUEL STATION

**konstal**  
GRUPA



## FOR WHOM?

Container fuel stations allow to refuel both **passenger cars and trucks, agricultural machinery, motor boats, yachts, helicopters and planes**. They are designed and manufactured to ensure storing and distributing fuels in accordance with ecological standards, while eliminating the potentially negative impact on the environment





## DESIGNATION OF CONTAINER STATION

Container fuel station is a comprehensive, modern, easy-to-use product that can be applied, among others in the following areas:

- as a self-service, easy to install, mobile fuel station
- as a fuel station for watercrafts increasing ecological safety,
- as a fuel station for a machine park and fleet, among others by truck transport companies, passenger transport, individual farmers or railways,
- as a mobile fuel distribution point for vehicles servicing investments related to the construction of road infrastructure (construction of roads and highways),
- as a fuel station for small and medium-sized airports, including private airports



## STANDARD EQUIPMENT

- Suction pipe DN 25 - DN 50 with mechanical or electromagnetical anti-siphon valve
- Filling pipe DN 50 - DN 100 with overfill prevention valve DN 50 and Camlock
- Venting pipe DN 50 with venting valve with flame arrester
- Vapor return pipe DN 15 - DN 25 from dispenser to the gasoline chamber, optional to diesel chamber
- Vapor return pipe DN 80 or DN 100 form the filling truck to gasoline chamber, ended with quick connector with flame arrester.
- Socket for manual measurement DN 50 ended with camlock quick connector
- Socket for automatic measurement DN 50 - DN 100 ended with internal thread (muff)
- Reserve socket DN 50 - DN 100 (muff)





## TECHNICAL SPECIFICATION OF THE CONTAINER

- Structure with sheathing of sandwich panels or trapezoidal plates
- Platform for a dispenser
- Roof over a platform with LED EX
- The roof of the container is covered with a waterproof anti-skid membrane
- Technical room with space for a computer, electrical switchboard and other accessories
- Electrical switchboard
- Staff room
- Upper lighting in staff and technical rooms



## ADDITIONAL CONTAINER CUSTOMIZATION OPTIONS

- LED lighting of the upper outline of a container
- Side LED lighting
- Possibility of extending the container with a shop module
- Possibility of covering the distribution platform with a tempered glass
- Possibility of covering a distribution platform with sandwich panels, with access to the distributor closed by external roller doors
- Adaptation of a tank for storage and distribution of aviation fuels
- Adaptation of a chamber for storage of AdBlue (application of an internal heater, external insulation of a tank and pipeline, and application of heating cables on a pipeline)
- Preparation of a niche for a compressor
- Roller measurement dipstick
- Instalation of a dispenser
- Installation of a payment terminal and price sign
- Installation of a price sign on a roof of container
- Adjustment of a container for solar panel application
- Application of graphics on external panels in accordance with submitted requirement (logo, company's name, etc.)



## TECHNICAL SPECIFICATION OF THE TANK

<b>general information</b>	<ul style="list-style-type: none"> <li>• preparation of the outer and internal surfaces by blasting to grade Sa 2.5 acc. to PN-EN ISO 8501-1</li> <li>• adaptation of the tank to the wet or dry method of leakage detection system</li> <li>• pipes made of stainless steel A1304</li> </ul>
<b>standard</b>	produced in accordance with EN 12285-2 or DIN 6616
<b>construction</b>	horizontal, cylindrical tank in container construction
<b>material</b>	certified carbon steel S235JR
<b>number of chambers</b>	from 1 to 6
<b>capacity (m<sup>3</sup>)</b>	from 10 to 80 m <sup>3</sup>
<b>diameter (mm)</b>	from 1600 to 2800 mm
<b>wall's structure</b>	double wall
<b>work temperature</b>	from -20°C to +50°C
<b>external coating</b>	polyurea paint C3 class in acc. PN-EN ISO 12944-2
<b>internal coating</b>	specialized paint coatings resistant to the properties of stored substances
<b>designation</b>	<ul style="list-style-type: none"> <li>• storage of liquid fuels (e.g. gasoline, diesel, synthetic fuels, biodiesel) and other liquid substances (e.g. washer fluid)</li> <li>• adaptable to the storage of AdBlue</li> <li>• adaptable to the storage of aviation fuel</li> </ul>





**Ekonstal**<sup>®</sup>  
GRUPA

**Manufacturer:**

Ekonstal Sp. z o.o.  
ul. Słoneczna 30  
88-230 Piotrków Kujawski, Poland

**Sales Office:**

ul. Słoneczna 21, 86-031 Osielsko, Poland  
+48 690 810 304  
sales@ekonstal.pl

**EKONSTAL.PL/EN/**